



Frequency: 3400-3800MHz

Gain: 8dBi

Power Rating:100W

Connector: N-Female

OVERVIEW

BRIDGE OMNI ANTENNAS are fully compatible with any Cellular, IoT, TETRA, WIFI, VHF and UHF network system. The antennas have a High-Band-Width 360° design and are made with high quality fiberglass and rugged elements, allowing the antennas to withstand outdoor environments.


KEY FEATURES

- N, Din and 4.3-10 connector are available upon request
- High gain and compact size
- Antennas have an IP protection rating of IP65 making them suitable for outdoor applications

TECHNICAL DATA

Electrical Specifications	
Frequency Range (MHz)	3400-3800MHz
Gain	8dBi
VSWR	≤1.8
Polarization	Vertical
Beamwidth- H	360°
Beamwidth- V	15°
Power Rating	100W
Impedance	50Ω

Product Pictures





Mechanical Specifications	
Connector	1XN-Female, Bottom
Dimensions	Φ20 x 600mm
Weight	0.7kg
Radome Color	Gray/White/Black
Radome Material	Fiber-reinforced plastic

Radiation Diagrams

Horizontal plane pattern

Vertical plane pattern



Environmental Specifications	
Wind Load	60m/s
Temperature	-40°C~+65°C
Humidity	≤95%
IP Rating	IP65
Lightning Protection	DC Ground

Installation Specifications	
Installation Method	Pole Mounting
Mounting Pole Diameter	Φ38- Φ52mm