

Frequency: 698-2700MHz

Gain: 3/5dBi

Power Rating: 50W

Connector: N-Female

OVERVIEW

BRIDGE OMNI ANTENNAS are fully compatible with any Cellular, IoT, TETRA, WIFI, VHF and UHF network system. The antennas have a High-Band-Width 360° design and are made with high quality fiberglass and rugged elements, allowing the antennas to withstand outdoor environments.

KEY FEATURES


- N, Din and 4.3-10 connector are available upon request
- High gain and compact size
- Antennas have an IP protection rating of IP65 making them suitable for outdoor applications

Product Pictures




Radiation Diagrams

Horizontal plane pattern



Vertical plane pattern



TECHNICAL DATA

Electrical Specifications

Frequency Range (MHz)	698-2700MHz
Gain	3/5dBi
VSWR	≤1.8
Polarization	Vertical
Beamwidth- H	360°
Beamwidth- V	25°±10°
Power Rating	50W
Impedance	50Ω

Mechanical Specifications

Connector	N-Female, Bottom
Dimensions	Φ60x250mm
Weight	0.74kg
Radome Color	Gray/White/Black
Radome Material	Fiber-reinforced plastic

Environmental Specifications

Wind Load	60m/s
Temperature	-40°C~+55°C
Humidity	≤95%
IP Rating	IP65
Lightning Protection	DC Ground

Installation Specifications

Installation Method	Pole Mounting
Mounting Pole Diameter	Φ10- Φ95mm